

Si photodiode S7878

High sensitivity X-ray detector



Features

- Ceramic scintillator for high sensitivity and reliability unlike CsI (ceramic scintillator: no deliquescence)
- 5 × 5 element photodiode array
- High sensitivity to X-rays: 1.8 times higher sensitivity than CWO
- Less afterglow: lower than CsI
<0.1 %/3 ms, <0.01 %/30 ms
- Low crosstalk structure

Applications

- X-ray fluorescence analysis
- X-ray detection

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Value	Unit
Reverse voltage	VR Max.	10	V
Operating temperature	Topr	-10 to +60	°C
Storage temperature	Tstg	-20 to +70	°C

■ Photodiode electrical and optical characteristics (Ta=25 °C, per element)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	320 to 1000	-	nm
Peak sensitivity wavelength	λ_p		-	800	-	nm
Photo sensitivity	S	$\lambda=510$ nm	0.33	0.38	-	A/W
		$\lambda=\lambda_p$	0.44	0.51	-	A/W
Dark current	Id	VR=10 mV	-	1.5	10	pA
Terminal capacitance	Ct	VR=0 V, f=10 kHz	-	20	-	pF

■ X-ray sensitivity (tube current: 1.0 mA, aluminum filter: t=6 mm, distance=830 mm)

X-ray tube voltage	Value	Unit
120 kV	1.2	nA

Note) Sensitivity values are just for your reference. Actual sensitivity values may vary depending on an equipment type and measurement conditions.

■ Dimensional outline (unit: mm)



KMPDA0097EA

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2004 Hamamatsu Photonics K.K.

Cat. No. KMPD1042E02
Jan. 2004 DN