




Dual Element Detector**LHi 778****TO-5 housing****Competitive cost version****Designed for motion control**

The **LHi 778** pyroelectric infrared-detector series are the standard dual element design recommended for all variants of motion control. They include a dual element pyro-electric ceramic element with Fet in source follower connection.

LHi 778 detector is available in **TO-5** housing with standard infrared filter. It provides high responsivity with excellent common mode performance (match) and low noise at steady state and temperature changes.



LHi 778					
Parameters	min	typical	max	units	condition
Element size		2x1		mm ²	2 elements
Responsivity	3-300	4000		V/W	100°C, 1 Hz
Match		1	10	%	
Noise		20	50	μVpp	25°C, 0,3...10Hz
Offset Voltage	0,2		1,55	V	R _s =47kΩ, 25°C
NEP		7,5x10 ⁻¹⁰	28x10 ⁻¹⁰	W √Hz	1Hz Bw, 100°C, 1 Hz
D*	5x10 ⁻⁷	19x10 ⁻⁷		cm √Hz/W	1Hz Bw, 100°C, 1 Hz
Output Impedance		5	10	kΩ	47kΩ Load Res.
Operating Voltage	2		15	V	R _s =47kΩ, 25°C
Operating Temperature	-40		85	°C	non permanent
Storage Temperature	-40		85	°C	non permanent

