

Vishay Semiconductors

94 8639

Silicon NPN Phototransistor

Description

BPW17N is a silicon NPN epitaxial planar phototransistor in a miniature plastic case with a \pm 12 $^\circ$ lens.

With a lead center to center spacing of 2.54 mm and a package width of 2.4 mm the devices are easily stackable on PC boards and assembled to arrays of unlimited size.

Due to its waterclear epoxy the device is sensitive to visible and near infrared radiation.

Features

- Miniature T-3/4 clear plastic package with lens
- Narrow viewing angle $\varphi = \pm 12^{\circ}$
- Insensitive against background light due to narrow aperture
- Suitable for 0.1\" (2.54 mm) center to center spacing
- Suitable for visible and near infrared radiation
- Compatible with IR diode CQY37N
- Lead-free device

Absolute Maximum Ratings

T _{amb} = 25 °C, unless otherwise specified				
Parameter	Test condition	Symbol	Value	Unit
Collector Emitter Voltage		V _{CEO}	32	V
Emitter Collector Voltage		V _{ECO}	5	V
Collector current		Ι _C	50	mA
Collector peak current	$t_p T = 0.5, t_p \le 10 \text{ ms}$	I _{CM}	100	mA
Total Power Dissipation	$T_{amb} \leq 55$ °C	P _{tot}	100	mW
Junction Temperature	\sim	Тj	100	°C
Storage Temperature Range		T _{stg}	- 55 to + 100	°C
Soldering Temperature	rt≤3 s	T _{sd}	260	°C
Thermal Resistance Junction/Ambient		R _{thJA}	450	K/W

Electrical Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Min	Тур.	Max	Unit
Collector Emitter Breakdown Voltage	I _C = 1 mA	V _{(BR)CEO}	32			V
Collector-emitter dark current	V _{CE} = 20 V, E = 0	I _{CEO}		1	200	nA
Collector-emitter capacitance	$V_{CE} = 5 V, f = 1 MHz, E = 0$	C _{CEO}		8		pF

Applications

Detector in electronic control and drive circuits

Vishay Semiconductors

Optical Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Min	Тур.	Max	Unit
Collector Light Current	$E_e = 1 \text{ mW/cm}^2$, $\lambda = 950 \text{ nm}$,	I _{ca}	0.5	1.0		mA
	$V_{CE} = 5 V$					
Angle of Half Sensitivity		φ		± 12	(deg
Wavelength of Peak Sensitivity		λ _p		825	\square	m
Range of Spectral Bandwidth		λ _{0.5}		620 to 960	70	nm
Collector Emitter Saturation	$E_e = 1 \text{ mW/cm}^2$, $\lambda = 950 \text{ nm}$,	V _{CEsat}			0.3	× ×
Voltage	I _C = 0.1 mA					\searrow
Turn-On Time	V_{S} = 5 V, I_{C} = 5 mA, R_{L} = 100 Ω	t _{on}		4.8	$\left(\left(\right) \right)$	μs
Turn-Off Time	V_{S} = 5 V, I_{C} = 5 mA, R_{L} = 100 Ω	t _{off}		5.0		μs
Cut-Off Frequency	V_S = 5 V, I_C = 5 mA, R_L = 100 Ω	f _c		120 ~	$[\land]$	kHz

Typical Characteristics (T_{amb} = 25 °C unless otherwise specified)











BPW17N Vishay Semiconductors



Fig. 5 Collector Light Current vs. Collector Emitter Voltage



Fig. 6 Collector Emitter Capacitance vs. Collector Emitter Voltage









BPW17N

Vishay Semiconductors

Package Dimensions in mm









Vishay Semiconductors

Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

- 1. Meet all present and future national and international statutory requirements.
- 2. Regularly and continuously improve the performance of our products, processes, distribution and operatingsystems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

- 1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
- 2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
- 3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B/and/C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423