


CLE300F

Aluminum Gallium Arsenide IRED Flat Lead PLCC Package



May, 2003



features

- Flat lead PLCC package
- $\pm 50^\circ$ emission angle
- 850 nm peak wavelength

description

The CLE300F is an 850nm high output infrared emitting diode chip featuring current AlGaAs technology. It is mounted in a compact, embedded leadframe package with flying lead configuration and overcoated with clear epoxy to provide a wide emission pattern. Contact Clairex for other options.

absolute maximum ratings ($T_A = 25^\circ\text{C}$ unless otherwise stated)

storage temperature	-40°C to +125°C
operating temperature	-40°C to +100°C
lead soldering temperature ⁽¹⁾	260°C
continuous forward current ⁽²⁾	50mA
peak forward current (1.0ms pulse width, 10% duty cycle)	1A
reverse voltage	5V
continuous power dissipation ⁽³⁾	80mW

notes:

1. 0.06" (1.5mm) from case for 5 seconds maximum.
2. Derate linearly 0.53mA/°C from 25°C free air temperature to $T_A = +100^\circ\text{C}$.
3. Derate linearly 0.85mW/°C from 25°C free air temperature to $T_A = +100^\circ\text{C}$.

electrical characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

symbol	parameter	min	typ	max	units	test conditions
P_O	Total power output	3.0	4.0	-	mW	$I_F = 20\text{mA}$
V_F	Forward voltage	-	1.4	1.6	V	$I_F = 20\text{mA}$
I_R	Reverse current	-	-	10	μA	$V_R = 5\text{V}$
λ_p	Peak emission wavelength	-	850	-	nm	$I_F = 20\text{mA}$
BW	Spectral bandwidth at half power points	-	60	-	nm	$I_F = 20\text{mA}$
θ_{HP}	Emission angle at half power points	-	100	-	deg.	$I_F = 20\text{mA}$
t_r	Radiation rise time ⁽⁴⁾	-	20	-	ns	$I_{F(PK)} = 20\text{mA}$
t_f	Radiation fall time ⁽⁴⁾	-	40	-	ns	$I_{F(PK)} = 20\text{mA}$

notes: 4. $f = 100\text{kHz}$, D.C. = 50%. Pulse generator t_r and $t_f < 200\text{ps}$.

Clairex reserves the right to make changes at any time to improve design and to provide the best possible

Revised 3/15/06

Clairex Technologies, Inc.
Phone: 972-265-4900

1301 East Plano Parkway
Fax: 972-265-4949

Plano, Texas 75074-8524
www.clairex.com