

TOSHIBA PHOTO DIODE SILICON PIN

TPS703, TPS704

SILICON PIN PHOTO DIODE FOR REMOTE CONTROL

VARIOUS KINDS OF REMOTE CONTROL SYSTEMS

SMOKE SENSOR


OPTICAL COMMUNICATION

- Detector for visible, fluorescent, and other disturbance light.
TPS703 : $\lambda > 700\text{nm}$
TPS704 : $\lambda > 800\text{nm}$
- High sensitivity
TPS703 : $I_{SC} = 1.5\mu\text{A}$ (Typ.)
TPS704 : $I_{SC} = 0.9\mu\text{A}$ (Typ.)
- High speed response : $t_r, t_f = 100\text{ns}$ (Typ.)
- Wide half value angle : $\theta \frac{1}{2} = \pm 65^\circ$ (Typ.)
- TLN105B, TLN115A, etc. are available as high radiant power infrared LEDs.


MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Reverse Voltage		V_R	20	V
Power Dissipation		P_D	150	mW
Power Dissipation Derating (Ta > 25°C)	TPS703	$\Delta P_D / ^\circ\text{C}$	-2.36	mW / °C
	TPS704		-4.3	
Operating Temperature Range	TPS703	T_{opr}	-30~80	°C
	TPS704		-30~60	
Storage Temperature Range	TPS703	T_{stg}	-40~90	°C
	TPS704		-40~60	
Soldering Temperature · Time		T_{sol}	260°C·3s	—

PRODUCT INDICATION



Unit in mm



() : REFERENCE VALUE

JEDEC	—
EIAJ	—
TOSHIBA	0-7B1

Weight : 0.31g (Typ.)

PIN CONNECTION



1. ANODE
2. CATHODE

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

OPTO-ELECTRICAL CHARACTERISTICS (Ta = 25°C)







CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Short Circuit Current		I_{SC}	E = 0.1mW / cm ² (Note)	TPS703	0.9	1.5	μ A
				TPS704	0.5	0.9	
Dark Current		I_D	$V_R = 10V, E = 0$	—	1	30	nA
Open Circuit Voltage		V_{OP}	E = 0.1mW / cm ² (Note)	TPS703	150	250	mV
Capacitance		C_T	$V_R = 3V, f = 1MHz$	—	20	—	pF
Peak Sensitivity Wavelength		λ_P	—	TPS703	—	960	nm
				TPS704	—	1000	
Switching Time	Rise Time	t_r	$V_R = 10V, R_L = 1k\Omega$	—	100	—	ns
	Fall Time	t_f		—	100	—	
Half Value Angle		$\theta_{\frac{1}{2}}$		—	± 65	—	°

Note : Color temperature = 2870°K, Standard Tungsten Lamp.




PRECAUTION

Please be careful of the followings.

1. Soldering shall be performed at a portion of lead above 2.3mm from the body of the device.
2. If the lead is formed, the lead should be formed at a distance of 2.3mm from the body of the device.
Soldering shall be performed after lead forming.



DIRECTIONAL SENSITIVITY CHARACTERISTIC
(TYP.) ($T_a = 25^\circ\text{C}$)



This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.

www.yc-dz.com