





PACKAGE DIMENSIONS inch (mm)



PRODUCT DESCRIPTION

Small area planar silicon photodiode in a lensed sidelooking package. The package material filters out visible light but passes infrared. These diodes exhibit low dark current under reverse bias and fast speed of response.

CASE 7 LATERAL
CHIP ACTIVE AREA: .0011 in² (0.684 mm²)

ABSOLUTE MAXIMUM RATINGS

Storage Temperature: -40°C to 85°C
Operating Temperature: -40°C to 85°C

ELECTRO-OPTICAL CHARACTERISTICS @ 25°C (See also VTP curves, pages 45-46)

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	VTP7210			UNITS
			Min.	Typ.	Max.	
I _{SC}	Short Circuit Current	H = 100 fc, 2850 K	5	7		μA
TC I _{SC}	I _{SC} Temperature Coefficient	2850 K		.26		%/°C
V _{OC}	Open Circuit Voltage	H = 100 fc, 2850 K		350		mV
TC V _{OC}	V _{OC} Temperature Coefficient	2850 K		-2.0		mV/°C
I _D	Dark Current	H = 0, V _R = 10 V			35	nA
R _{SH}	Shunt Resistance	H = 0, V = 10 mV		7		GΩ
C _J	Junction Capacitance	H = 0, V = 3 V			25	pF
Re	Responsivity	940 nm		.015		A/(W/cm ²)
S _R	Sensitivity	@ Peak		.55		A/W
λ _{range}	Spectral Application Range		700		1150	nm
λ _p	Spectral Response >Peak			925		nm
V _{BR}	Breakdown Voltage		30	140		V
θ _{1/2}	Angular Resp. - 50% Resp. Pt.			±58		Degrees
NEP	Noise Equivalent Power			1.9 x 10 ⁻¹³ (Typ.)		W/√Hz
D*	Specific Detectivity			5.3 x 10 ¹¹ (Typ.)		cm√Hz/W