


## Description

The MIM-5xxBS3F is miniaturized infrared receivers for remote control and other applications requiring improved ambient light rejection.

The separate PIN diode and preamplifier IC are assembled on a single leadframe.

The epoxy package contains a special IR filter.

This module has excellent performance even in disturbed ambient light applications and provides protection against uncontrolled output pulses.




## Features

- | Photo detector and preamplifier in one package
- | Internal filter for PCM frequency
- | High immunity against ambient light
- | Improved shielding against electric field disturbance
- | 5.0-Volt supply voltage; low power consumption
- | TTL and CMOS compatibility

## MIM-5xxBS3F Series Models

- |                     |                     |
|---------------------|---------------------|
| MIM-530BS3F 30.0KHz | MIM-538BS3F 38.0KHz |
| MIM-533BS3F 33.0KHz | MIM-540BS3F 40.0KHz |
| MIM-536BS3F 36.0KHz | MIM-544BS3F 44.0KHz |
| MIM-537BS3F 36.7KHz | MIM-556BS3F 56.0KHz |

## BLOCK DIAGRAM



# INFRARED RECEIVER MODULE

MIM-5xxBS3F

## Absolute Maximum Ratings

@ Ta=25°C

Item	Symbol	Ratings	Unit	Remark
Supply voltage	V <sub>CC</sub>	-0.3 ~ 6.0	V	
Supply Current	I <sub>S</sub>	5.0	mA	
Operating temperature	T <sub>opr</sub>	-25 ~ +85	°C	
Storage temperature	T <sub>stg</sub>	-25 ~ +85	°C	
Soldering temperature	T <sub>sd</sub>	260	°C	t≤5 s, 1mm from case
Power dissipation at Ta=25°C	P <sub>tot</sub>	30	mW	

## Electro-optical characteristics (Vcc=5.0V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remarks
Supply Voltage	V <sub>s</sub>	4.5	5.0	5.5	V	
Current consumption	I <sub>cc</sub>		1.4	2.0	mA	Under no signal
Response wavelength	λ <sub>p</sub>		940		nm	
Output form	----- active low output -----					
H level output voltage	V <sub>0h</sub>	4.2			V	
L level output voltage	V <sub>0l</sub>			0.5	V	
H level output pulse width	T <sub>wh</sub>	400		800	μs	
L level output pulse width	T <sub>wl</sub>	400		800	μs	
Distance between emitter & detector	L <sub>1</sub>	10.0			m	Note 1
Half angle	Δθ		±45		deg	Horizontal direction

## Test Method

### A. Standard Transmitter




Fig 1. Burst Wave






Fig 2. Standard Transmitter Measurement circuit


## B. Detection Length Test




## C . Pulse Width Test




## Application Circuit




\*) recommended to suppress power supply disturbances

**Dimensions in mm**P.S. 1. TOLERANCE :  $\pm 0.3$  UNLESS OTHERWISE SPECIFIED


## CHARACTERISTIC CURVES ( $T_A=25^\circ\text{C}$ )




SUPPLY VOLTAGE vs. SUPPLY CURRENT




RELATIVE TRANSMISSION DISTANCE



FREQUENCY DEPENDENCE OF RESPONSIVITY



INPUT LEVEL vs. OUTPUT PULSE WIDTH



RELATIVE SPECTRAL SENSITIVITY vs WAVELENGTH

**Reliability**

Test item	Test condition	Standard
High temperature	Ta=+80°C t=240H	Note 2.
High temp. & high humi.	Ta=+40°C 90%RH t=240H	Note 2.
Low temperature	Ta= -30°C t=240H	Note 2.
Temperature cycle	-30°C(0.5H) ~ +80°C(0.5H) 20cycle	Note 2.
Dropping	Test devices shall be dropped 3 times naturally onto hard wooden board from a 75cm height position.	Note 3.

NOTE 1. Distance between emitter & detector specifies maximum distance that output wave form satisfies the standard under the conditions below against the standard transmitter.

- (1) Measuring place ..... Indoor without extreme reflection of light.
- (2) Ambient light source... Detecting surface illumination shall be  $200\pm50$ Lux under ordinary

hite fluorescene lamp of no high frequency lighting.

- (3) Standard transmitter ... Burst wave indicated in Fig 1. of standard transmitter shall be arranged to 50mVp-p under the measuring circuit specified in Fig 2.

NOTE 2. (electro-optical characteristics) shall be satisfied after leaving 2 hours in the normal temperature .

NOTE 3. (electro-optical characteristics) shall be satisfied and no conoid deforms and destructions of appearance .(excepting deforms of terminals)

**Inspection standard**

1. Among electrical characteristics , total number shall be inspected on items blow.

- 1-1 front distance between emitter & detector
- 1-2 Current consumption
- 1-3 H level output voltage
- 1-4 L level output voltage

2. Items except above mentioned are not inspected particularly , but shall fully satisfy

**CAUTION ( When use and storage of this device )**

- 1. Store and use where there is no force causing transformation or change in quality .
- 2. Store and use where there is no corrosive gas or sea(salt) breeze .
- 3. Store and use where there is no extreme humidity .
- 4. Solder the lead-pin within the condition of ratings. After soldering do not add extra force .
- 5. Do not wash this device . Wipe the stains of diode side with a soft cloth. You can use the solvent , ethylalcohol or methylalcohol or isupropylene only .
- 6. To prevent static electricity damage to the Pre-AMP make sure that the human body , the soldering iron is connected to ground before using .
- 7. Put decoupling device between Vcc and GND for reduse the noise from power supply line .
- 8. The performance of remote-control system depends on environments condition and ability of periferal parts. Customer should evaluate the performance as total system in those conditions after system up with components such as commander , micon and this receiver module .

**Others**

- 1. This device is not design to endure radiative rays and heavily charged particles .
- 2. In case where any trouble or questions arise,both parties agree to make full discussion covering the said problem .