

Violet Laser Diode NDV4212

■ Features

- Optical Output Power: CW100mW Pulse180mW
- Can Type: ϕ 5.6 Floating Mounted
- Peak Wavelength: 405nm

■ Absolute Maximum Ratings

(Tc=25°C)

Item	Symbol	Absolute Maximum Ratings	Unit
Optical Output Power	CW	P _{oc}	120 mW
	Pulse	P _{op}	200* mW
LD Reverse Voltage	V _r (LD)	2	V
Storage Temperature	T _{stg}	-40 ~ 85	°C
Operating Case Temperature	T _c	-10 ~ 80	°C

* Pulse Condition: Pulse Width 30ns, Duty 50%

■ Initial Electrical/Optical Characteristics

(Tc=25°C)

Item	Condition	Symbol	Min	Typ.	Max	Unit
Optical Output Power	CW	P _o	-	-	100	mW
Peak Wavelength*	P _o =100mW	λ_p	400	405	410	nm
Threshold Current	CW	I _{th}	-	35	50	mA
Operating Current	P _o =100mW	I _{op}	-	100	130	mA
Slope Efficiency	CW	η	1.2	1.4	1.9	W/A
Operating Voltage	P _o =100mW	V _{op}	-	4.6	5.5	V
FWHM Beam Divergence*	P _o =100mW	$\theta_{//}$	7.0	9.0	12.0	deg.
		$\theta_{\perp}$	15.0	19.5	23.0	deg.
Emission Point Accuracy	Angle P _o =100mW	$\Delta\theta_{//}$	-	-	± 2	deg.
		$\Delta\theta_{\perp}$	-	-	± 2.5	deg.

* Measuring specifications


All figures in this specification are measured by Nichia's method and may contain measurement deviations.

The above specifications are for reference purpose only and subjected to change without prior notice.

Outline Dimension



Pin Connection



This model does not have Phase 3

Safety of Laser light

- Laser Light can damage the human eyes and skin. Do not expose the eye or skin to any laser light directly and/or through optical lens. When handling the LDs, wear appropriate safety glasses to prevent laser light, even any reflections from entering to the eye. Focused laser beam through optical instruments will increase the chance of eye hazard.
- These LDs are classified in Class 4 of IEC60825-1 and 21 CFR Part 1040.10 Safety Standards. It is absolutely necessary to take overall safety measures against User's modules, equipment and systems into which Nichia LDs are incorporated and/or integrated.

