

GP1S50/GP1S51 /GP1S52

Compact Photointerrupter

T-41-73

■ Features


1. Compact type
2. High sensing accuracy (Slit width : 0.5mm)
3. Both-sides mounting type : GP1S50
Either-side mounting type : GP1S51
PWB direct mounting type : GP1S52

■ Applications

1. OA equipment, such as FDDs, printers, facsimiles
2. VCRs

■ Outline Dimensions

(Unit : mm)



SHARP

657

■ Absolute Maximum Ratings

(Ta=25°C)

T-41-73

	Parameter	Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	*1 Peak forward current	I_{FM}	1	A
	Reverse voltage	V_R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	I_C	20	mA
	Collector power dissipation	P_C	75	mW
	Operating temperature	T_{OPR}	-25 ~ +85	°C
	Storage temperature	T_{STG}	-40 ~ +100	°C
	*2 Soldering temperature	T_{SOL}	260	°C

*1 Puls width $\leq 100\mu s$, Duty ratio = 0.01

*2 For 5 seconds

■ Electro-optical Characteristics

(Ta=25°C)

	Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V_F	$I_F = 20\text{mA}$	—	1.25	1.4	V
	Peak forward voltage	V_{FM}	$I_{FM} = 0.5\text{A}$	—	3	4	V
	Reverse current	I_R	$V_R = 3\text{V}$	—	—	10	μA
Output	Collector dark current	I_{CEO}	$V_{CE} = 20\text{V}$	—	10^{-9}	10^{-7}	A
Transfer characteristics	Current transfer ratio	CTR	$I_F = 20\text{mA}$, $V_{CE} = 5\text{V}$	2.5	—	25	%
	Collector-emitter saturation voltage	$V_{CE(SAT)}$	$I_F = 40\text{mA}$, $I_C = 0.5\text{mA}$	—	—	0.4	V
	Response time (Rise)	t_R	$V_{CE} = 2\text{V}$, $I_C = 2\text{mA}$	—	3	15	μs
	Response time (Fall)	t_F	$R_L = 100\Omega$	—	4	20	μs

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature











Fig. 3 Peak Forward Current vs. Duty Ratio**Fig. 4 Forward Current vs. Forward Voltage****Fig. 5 Collector Current vs. Forward Current****Fig. 6 Collector Current vs. Collector-emitter Voltage****Fig. 7 Collector Current vs. Ambient Temperature****Fig. 8 Collector-emitter Saturation Voltage vs. Ambient Temperature**

Fig. 9 Response Time vs. Load Resistance

T-41-73



Test Circuit for Response Time




Fig. 10 Frequency Response




Fig. 11 Collector Dark Current vs. Ambient Temperature




Fig. 12 Relative Collector Current vs. Shield Distance (1)




Fig. 13 Relative Collector Current vs. Shield Distance (2)

