

PT501/PT510

TO-18 Type Narrow Acceptance Phototransistor

■ Features


1. Narrow acceptance ($\Delta\theta$: TYP. $\pm 6^\circ$)
2. TO -18 type standard package
3. With base terminal : **PT510**

■ Applications

1. Optoelectronic switches, optoelectronic counters
2. Smoke detectors
3. Infrared applied systems

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter	Symbol	PT501	PT510	Unit
Collector-emitter voltage	V_{CEO}	45	35	V
Emitter-collector voltage	V_{ECO}	6	6	V
Collector-base voltage	V_{CBO}	-	35	V
Emitter-base voltage	V_{EBO}	-	6	V
Collector power dissipation	P_C	75	75	mW
Operating temperature	T_{opr}	- 25 to + 125	- 25 to + 125	°C
Storage temperature	T_{stg}	- 55 to + 150	- 55 to + 150	°C
*1 Soldering temperature	T_{sol}	260	260	°C

*1 For 10 seconds at the position of 1.3mm from the bottom face of can package

■ Electro-optical Characteristics

(Ta = 25°C)

Parameter		Symbol	Conditions	MIN.	TYP.		MAX.	Unit
*2Collector current		I _C	V _{CE} = 5V, E _e = 10mW/cm ²	2.5	PT501	10	-	mA
					PT510	20		
Collector dark current		I _{CEO}	V _{CE} = 30V, E _e = 0	-	2 x 10 ⁻⁹		10 ⁻⁷	A
*2Collector-emitter saturation voltage		V _{CE (sat)}	I _C = 1mA, E _e = 10mW/cm ²	-	0.2		-	V
Peak sensitivity wavelength		λ _p		-	800		-	nm
Response time	Rise time	t _r	V _{CE} = 2V, I _C = 2mA, R _L = 100Ω (PT501: 1kΩ)	-	PT501	10	-	μs
					PT510	2		
	Fall time	t _f		-	PT501	10	-	μs
					PT510	3		

*2 E_e : Irradiance by CIE standard light source A (tungsten lamp)

*2 Classification Table of Collector Current(I_C)

Model No.	I _C (mA)
PT501A	20 to 80
PT501B	10 to 25
PT501C	2.5 to 15

at V_{CE}= 5V, E_e = 10mW/cm², Ta = 25°C

Fig. 1 Collector Power Dissipation vs. Ambient Temperature




Fig. 2 Collector Dark Current vs. Ambient Temperature




Fig. 3 Relative Collector Current vs. Ambient Temperature




Fig.4-a Collector Current vs. Irradiance (PT501)




Fig.4-b Collector Current vs. Irradiance (PT510)




Fig.5-a Collector Current vs. Collector-emitter Voltage (PT510)




Fig.5-b Collector Current vs. Collector-emitter Voltage (PT510)




Fig. 6 Spectral Sensitivity




Fig. 7 Response Time vs. Load Resistance





Fig. 8 Response Time vs. Base Resistance (PT510)



Test Circuit for Response Time




Fig. 9 Sensitivity Diagram (Ta = 25°C)





Fig.10 Collector-emitter Saturation Voltage vs. Irradiance



● Please refer to the chapter “Precautions for Use.”