


Request For Quotation

Order the parts you need from our real-time inventory database. Simply complete a request for quotation form with your part information and a sales representative will respond to you with price and availability.

[Request For Quotation](#)

Your free datasheet starts on the next page.

More datasheets and data books are available from our homepage: <http://www.datasheetarchive.com>


SIEMENS**SFH 431 SERIES****INFRARED EMITTER****FEATURES**

- TO-18 Hermetic Package, 3-Leaded
- Dome Glass Lens
- Very Narrow Beam, $\pm 8^\circ$
- Three High Power Intensity Ranges
 - SFH 431 10 mW/Sr
 - SFH 431-1 10–20 mW/Sr
 - SFH 431-2 16–32 mW/Sr
 - SFH 431-3 ≥ 25 mW/Sr
- Reversed Polarity Compared to SFH 401
- GaAs Material

DESCRIPTION

The SFH 431 is a GaAs infrared emitting diode which emits radiation in the near infrared range. The emitted radiation, which can be modulated, is caused by current in the forward direction. The SFH 431 comes in a 3-leaded TO-18 package and has a glass lens to provide a narrow emitting beam. The cathode lead is the lead closest to the tab. The cathode is electrically connected to the case. The SFH 431 is electrically similar to the SFH 401 series, but has a reversed pin out and case polarity

Package Dimensions in Inches (mm)

**Absolute Maximum Ratings**

Parameter	Symbol	Min	Max	Unit
Power Dissipation			470	mW
DC Forward Current	I_F		300	mA
Surge Current ($t < 10 \mu s$, $D = 0$)			3.0	A
Reverse Voltage	V_R		5.0	V
Storage Temperature	T_S	-55	100	$^\circ C$
Operating Temperature	T_A	-55	100	$^\circ C$
Junction Temperature	T_J		100	$^\circ C$
Lead Soldering Temperature			260 $^\circ C$ for 5 sec	
(1/8 inch from case)				

Electrical Characteristics ($T_{amb} = 25^\circ C$)

Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions
Forward Voltage	V_F		1.3	1.5	V	$I_F = 100$ mA
Forward Voltage	V_F		1.9	2.5	V	$I_F = 1$ A
Reverse Current	I_R		0.01	10	μA	$V_R = 5$ V
Peak Wavelength	λ_p	930	950	970	nm	$I_F = 100$ mA
Half Angle	φ		± 8		Deg	

The diodes are grouped according to their radiant intensity I_e in axial direction (at $I_F = 100$ mA, $t_p = 20$ ms).

Dash Number	SFH431	-1	-2	-3	Unit
Radiant Intensity I_e	10	10–20	16–32	≥ 25	mW/Sr
Φ_e (Total) typ	6	5	6	7	mW

Radiant Characteristics $I_{rel} = f(\varphi)$ 