

## 74F161A • 74F163A

### Synchronous Presettable Binary Counter

#### General Description

The 74F161A and 74F163A are high-speed synchronous modulo-16 binary counters. They are synchronously presettable for application in programmable dividers and have two types of Count Enable inputs plus a Terminal Count output for versatility in forming synchronous multi-stage counters. The 74F161A has an asynchronous Master-Reset input that overrides all other inputs and forces the outputs LOW. The 74F163A has a Synchronous Reset input that overrides counting and parallel loading and allows the outputs to be simultaneously reset on the rising edge of the clock. The 74F161A and 74F163A are high-speed versions of the 74F161 and 74F163.

#### Features



- Synchronous counting and loading
- High-speed synchronous expansion
- Typical count frequency of 120 MHz

#### Ordering Code:





| Order Number | Package Number | Package Description                                                         |
|--------------|----------------|-----------------------------------------------------------------------------|
| 74F161ASC    | M16A           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow |
| 74F161ASJ    | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74F161APC    | N16E           | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide       |
| 74F163ASC    | M16A           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow |
| 74F163ASJ    | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74F163APC    | N16E           | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide       |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

#### Connection Diagrams



## Logic Symbols



## Unit Loading/Fan Out

| Pin Names                 | Description                                  | U.L.<br>HIGH/LOW | Input $I_{IH}/I_{IL}$<br>Output $I_{OH}/I_{OL}$ |
|---------------------------|----------------------------------------------|------------------|-------------------------------------------------|
| CEP                       | Count Enable Parallel Input                  | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| CET                       | Count Enable Trickle Input                   | 1.0/2.0          | 20 $\mu$ A/-1.2 mA                              |
| CP                        | Clock Pulse Input (Active Rising Edge)       | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| $\overline{MR}$ (74F161A) | Asynchronous Master Reset Input (Active LOW) | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| $\overline{SR}$ (74F163A) | Synchronous Reset Input (Active LOW)         | 1.0/2.0          | 20 $\mu$ A/-1.2 mA                              |
| $P_0$ - $P_3$             | Parallel Data Inputs                         | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| $\overline{PE}$           | Parallel Enable Input (Active LOW)           | 1.0/2.0          | 20 $\mu$ A/-1.2 mA                              |
| $Q_0$ - $Q_3$             | Flip-Flop Outputs                            | 50/33.3          | -1 mA/20 mA                                     |
| TC                        | Terminal Count Output                        | 50/33.3          | -1 mA/20 mA                                     |

## Functional Description

The 74F161A and 74F163A count in modulo-16 binary sequence. From state 15 (HHHH) they increment to state 0 (LLLL). The clock inputs of all flip-flops are driven in parallel through a clock buffer. Thus all changes of the Q outputs (except due to Master Reset of the 74F161A) occur as a result of, and synchronous with, the LOW-to-HIGH transition of the CP input signal. The circuits have four fundamental modes of operation, in order of precedence: asynchronous reset (74F161A), synchronous reset (74F163A), parallel load, count-up and hold. Five control inputs—Master Reset (MR, 74F161A), Synchronous Reset (SR, 74F163A), Parallel Enable (PE), Count Enable Parallel (CEP) and Count Enable Trickle (CET)—determine the mode of operation, as shown in the Mode Select Table. A LOW signal on MR overrides all other inputs and asynchronously forces all outputs LOW. A LOW signal on SR overrides counting and parallel loading and allows all outputs to go LOW on the next rising edge of CP. A LOW signal on PE overrides counting and allows information on the Parallel Data (P<sub>n</sub>) inputs to be loaded into the flip-flops on the next

rising edge of CP. With  $\overline{PE}$  and  $\overline{MR}$  (74F161A) or  $\overline{SR}$  (74F163A) HIGH, CEP and CET permit counting when both are HIGH. Conversely, a LOW signal on either CEP or CET inhibits counting.

The 74F161A and 74F163A use D-type edge triggered flip-flops and changing the  $\overline{SR}$ ,  $\overline{PE}$ , CEP and CET inputs when the CP is in either state does not cause errors, provided that the recommended setup and hold times, with respect to the rising edge of CP, are observed.

The Terminal Count (TC) output is HIGH when CET is HIGH and the counter is in state 15. To implement synchronous multi-stage counters, the TC outputs can be used with the CEP and CET inputs in two different ways. Please refer to the 74F568 data sheet. The TC output is subject to decoding spikes due to internal race conditions and is therefore not recommended for use as a clock or asynchronous reset for flip-flops, counters or registers.

Logic Equations: Count Enable = CEP • CET •  $\overline{PE}$

$$TC = Q_0 \cdot Q_1 \cdot Q_2 \cdot Q_3 \cdot CET$$

## Mode Select Table

| $\overline{SR}$<br>(Note 1) | $\overline{PE}$ | CET | CE<br>P | Action on the Rising<br>Clock Edge (↗) |
|-----------------------------|-----------------|-----|---------|----------------------------------------|
| L                           | X               | X   | X       | Reset (Clear)                          |
| H                           | L               | X   | X       | Load (P <sub>n</sub> →Q <sub>n</sub> ) |
| H                           | H               | H   | H       | Count (Increment)                      |
| H                           | H               | L   | X       | No Change (Hold)                       |
| H                           | H               | X   | L       | No Change (Hold)                       |


H = HIGH Voltage Level

L = LOW Voltage Level


X = Immaterial

Note 1: For 74F163A only

## State Diagram



## Block Diagram



**Absolute Maximum Ratings** (Note 2)

|                                                                        |                                      |
|------------------------------------------------------------------------|--------------------------------------|
| Storage Temperature                                                    | −65°C to +150°C                      |
| Ambient Temperature under Bias                                         | −55°C to +125°C                      |
| Junction Temperature under Bias                                        | −55°C to +150°C                      |
| V <sub>CC</sub> Pin Potential to Ground Pin                            | −0.5V to +7.0V                       |
| Input Voltage (Note 3)                                                 | −0.5V to +7.0V                       |
| Input Current (Note 3)                                                 | −30 mA to +5.0 mA                    |
| Voltage Applied to Output<br>in HIGH State (with V <sub>CC</sub> = 0V) |                                      |
| Standard Output                                                        | −0.5V to V <sub>CC</sub>             |
| 3-STATE Output                                                         | −0.5V to +5.5V                       |
| Current Applied to Output<br>in LOW State (Max)                        | twice the rated I <sub>OL</sub> (mA) |
| ESD Last Passing Voltage (Min)                                         | 4000V                                |

**Recommended Operating Conditions**

|                              |                |
|------------------------------|----------------|
| Free Air Ambient Temperature | 0°C to +70°C   |
| Supply Voltage               | +4.5V to +5.5V |

**Note 2:** Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

**Note 3:** Either voltage limit or current limit is sufficient to protect inputs.

**DC Electrical Characteristics**

| Symbol           | Parameter                         | Min                                       | Typ        | Max          | Units | V <sub>CC</sub> | Conditions                                                                                                                  |
|------------------|-----------------------------------|-------------------------------------------|------------|--------------|-------|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| V <sub>IH</sub>  | Input HIGH Voltage                | 2.0                                       |            |              | V     |                 | Recognized as a HIGH Signal                                                                                                 |
| V <sub>IL</sub>  | Input LOW Voltage                 |                                           |            | 0.8          | V     |                 | Recognized as a LOW Signal                                                                                                  |
| V <sub>CD</sub>  | Input Clamp Diode Voltage         |                                           |            | 1.2          | V     | Min             | I <sub>IN</sub> = −18 mA                                                                                                    |
| V <sub>OH</sub>  | Output HIGH Voltage               | 10% V <sub>CC</sub><br>5% V <sub>CC</sub> | 2.5<br>2.7 |              | V     | Min             |                                                                                                                             |
| V <sub>OL</sub>  | Output LOW Voltage                | 10% V <sub>CC</sub>                       |            | 0.5          | V     | Min             | I <sub>OL</sub> = 20 mA                                                                                                     |
| I <sub>IH</sub>  | Input HIGH Current                |                                           |            | 5.0          | μA    | Max             | V <sub>IN</sub> = 2.7V                                                                                                      |
| I <sub>bvi</sub> | Input HIGH Current Breakdown Test |                                           |            | 7.0          | μA    | Max             | V <sub>IN</sub> = 7.0V                                                                                                      |
| I <sub>CEX</sub> | Output HIGH Leakage Current       |                                           |            | 50           | μA    | Max             | V <sub>OUT</sub> = V <sub>CC</sub>                                                                                          |
| V <sub>ID</sub>  | Input Leakage Test                | 4.75                                      |            |              | V     | 0.0             | I <sub>ID</sub> = 1.9 μA<br>All Other Pins Grounded                                                                         |
| I <sub>OD</sub>  | Output Leakage Circuit Current    |                                           |            | 3.75         | μA    | 0.0             | V <sub>IOD</sub> = 150 mV<br>All Other Pins Grounded                                                                        |
| I <sub>IL</sub>  | Input LOW Current                 |                                           |            | −0.6<br>−1.2 | mA    | Max<br>Max      | V <sub>IN</sub> = 0.5V (CEP, CP, $\overline{MR}$ , P <sub>0</sub> –P <sub>3</sub> )<br>V <sub>IN</sub> = 0.5V (CET, PE, SR) |
| I <sub>OS</sub>  | Output Short-Circuit Current      | −60                                       |            | −150         | mA    | Max             | V <sub>OUT</sub> = 0V                                                                                                       |
| I <sub>CC</sub>  | Power Supply Current              |                                           | 37         | 55           | mA    | Max             |                                                                                                                             |


## AC Electrical Characteristics

| Symbol           | Parameter                                           | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      |      | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      | Units |
|------------------|-----------------------------------------------------|-----------------------------------------------------------------------------|------|------|---------------------------------------------------------------------------------------|------|------------------------------------------------------------------------------------|------|-------|
|                  |                                                     | Min                                                                         | Typ  | Max  | Min                                                                                   | Max  | Min                                                                                | Max  |       |
| t <sub>MAX</sub> | Maximum Count Frequency                             | 100                                                                         | 120  |      | 75                                                                                    |      | 90                                                                                 |      | MHz   |
| t <sub>PLH</sub> | Propagation Delay                                   | 3.5                                                                         | 5.5  | 7.5  | 3.5                                                                                   | 9.0  | 3.5                                                                                | 8.5  | ns    |
| t <sub>PHL</sub> | CP to Q <sub>n</sub> (PE Input HIGH)                | 3.5                                                                         | 7.5  | 10.0 | 3.5                                                                                   | 11.5 | 3.5                                                                                | 11.0 |       |
| t <sub>PLH</sub> | Propagation Delay                                   | 4.0                                                                         | 6.0  | 8.5  | 4.0                                                                                   | 10.0 | 4.0                                                                                | 9.5  | ns    |
| t <sub>PHL</sub> | CP to Q <sub>n</sub> (PE Input LOW)                 | 4.0                                                                         | 6.0  | 8.5  | 4.0                                                                                   | 10.0 | 4.0                                                                                | 9.5  |       |
| t <sub>PLH</sub> | Propagation Delay                                   | 5.0                                                                         | 10.0 | 14.0 | 5.0                                                                                   | 16.5 | 5.0                                                                                | 15.0 | ns    |
| t <sub>PHL</sub> | CP to TC                                            | 5.0                                                                         | 10.0 | 14.0 | 5.0                                                                                   | 15.5 | 5.0                                                                                | 15.0 |       |
| t <sub>PLH</sub> | Propagation Delay                                   | 2.5                                                                         | 4.5  | 7.5  | 2.5                                                                                   | 9.0  | 2.5                                                                                | 8.5  | ns    |
| t <sub>PHL</sub> | CET to TC                                           | 2.5                                                                         | 4.5  | 7.5  | 2.5                                                                                   | 9.0  | 2.5                                                                                | 8.5  |       |
| t <sub>PHL</sub> | Propagation Delay<br>MR to Q <sub>n</sub> (74F161A) | 5.5                                                                         | 9.0  | 12.0 | 5.5                                                                                   | 14.0 | 5.5                                                                                | 13.0 | ns    |
| t <sub>PHL</sub> | Propagation Delay<br>MR to TC (74F161A)             | 4.5                                                                         | 8.0  | 10.5 | 4.5                                                                                   | 12.5 | 4.5                                                                                | 11.5 | ns    |

## AC Operating Requirements



| Symbol             | Parameter                           | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V |     | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V |     | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V |     | Units |
|--------------------|-------------------------------------|---------------------------------------------------|-----|-------------------------------------------------------------|-----|----------------------------------------------------------|-----|-------|
|                    |                                     | Min                                               | Max | Min                                                         | Max | Min                                                      | Max |       |
| t <sub>S</sub> (H) | Setup Time, HIGH or LOW             | 5.0                                               |     | 5.5                                                         |     | 5.0                                                      |     | ns    |
| t <sub>S</sub> (L) | P <sub>n</sub> to CP                | 5.0                                               |     | 5.5                                                         |     | 5.0                                                      |     |       |
| t <sub>H</sub> (H) | Hold Time, HIGH or LOW              | 2.0                                               |     | 2.5                                                         |     | 2.0                                                      |     |       |
| t <sub>H</sub> (L) | P <sub>n</sub> to CP                | 2.0                                               |     | 2.5                                                         |     | 2.0                                                      |     |       |
| t <sub>S</sub> (H) | Setup Time, HIGH or LOW             | 11.0                                              |     | 13.5                                                        |     | 11.5                                                     |     | ns    |
| t <sub>S</sub> (L) | PE or SR to CP                      | 8.5                                               |     | 10.5                                                        |     | 9.5                                                      |     |       |
| t <sub>H</sub> (H) | Hold Time, HIGH or LOW              | 2.0                                               |     | 3.6                                                         |     | 2.0                                                      |     |       |
| t <sub>H</sub> (L) | PE or SR to CP                      | 0                                                 |     | 0                                                           |     | 0                                                        |     |       |
| t <sub>S</sub> (H) | Setup Time, HIGH or LOW             | 11.0                                              |     | 13.0                                                        |     | 11.5                                                     |     | ns    |
| t <sub>S</sub> (L) | CEP or CET to CP                    | 5.0                                               |     | 6.0                                                         |     | 5.0                                                      |     |       |
| t <sub>H</sub> (H) | Hold Time, HIGH or LOW              | 0                                                 |     | 0                                                           |     | 0                                                        |     |       |
| t <sub>H</sub> (L) | CEP or CET to CP                    | 0                                                 |     | 0                                                           |     | 0                                                        |     |       |
| t <sub>W</sub> (H) | Clock Pulse Width (Load)            | 5.0                                               |     | 5.0                                                         |     | 5.0                                                      |     | ns    |
| t <sub>W</sub> (L) | HIGH or LOW                         | 5.0                                               |     | 5.0                                                         |     | 5.0                                                      |     | ns    |
| t <sub>W</sub> (H) | Clock Pulse Width (Count)           | 4.0                                               |     | 5.0                                                         |     | 4.0                                                      |     |       |
| t <sub>W</sub> (L) | HIGH or LOW                         | 6.0                                               |     | 8.0                                                         |     | 7.0                                                      |     | ns    |
| t <sub>W</sub> (L) | MR Pulse Width, LOW<br>(74F161A)    | 5.0                                               |     | 5.0                                                         |     | 5.0                                                      |     | ns    |
| t <sub>REC</sub>   | Recovery Time<br>MR to CP (74F161A) | 6.0                                               |     | 6.0                                                         |     | 6.0                                                      |     | ns    |

# Physical Dimensions inches (millimeters) unless otherwise noted




**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow  
Package Number M16A**


# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



LAND PATTERN RECOMMENDATION




DIMENSIONS ARE IN MILLIMETERS



## NOTES:

- A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.


M16DRevB1



DETAIL A

16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M16D

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide  
Package Number N16E

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)